

Kubota

**U10-3**

**New Kubota mini-excavator**

**FOR EARTH,  
FOR LIFE**





# The U10-3 sets the standard for all ultra-compact excavators.

SPECIOUS, COMFORTABLE, AND MORE PRODUCTIVE, YET IT FITS IN THE TIGHTEST SPACES.

## Spacious legroom

The spacious legroom contributes to making the operator feel more at ease during operations.



## Zero tail swing


Zero tail swing prevents any damage from occurring to the engine cover, allowing the operator to focus more on the job at hand.

TURNING RADIUS  
500mm

## Tow speed travel

Step on the high speed pedal, and you'll maneuver around job sites faster.

Travel speed (Low/High):  
2.0/4.0km/h



## Working range

The U10's excellent reach and digging depth ensure that each digging job is performed with maximum efficiency and speed.


Max.digging  
depth: 1,800mm

Max.digging  
radius: 3,380mm

## Kubota engine

Powerful and dependable, the U10's diesel engine delivers superior horsepower and performance. It offers low noise and vibration levels, exceptional fuel efficiency.

Output: 7.4kW(10.2HP)



## Variable track width

The U10 features a hydraulic track gauge that can be adjusted to between 750mm to 990mm. With the touch of a single lever, you can reduce the track gauge to navigate narrow spaces or increase it to improve functionality.







## Foldable ROPS \*Optional

Rollover protective structure provides you with an extra measure of safety. It folds down to make easier transporting and storage of the excavator.



## Seat slide (ROPS version)

You will truly appreciate the comfort of its operator's seat with slide.

## Retractable seat belt (ROPS version)

The retractable seat belt holds operator's body securely.

## Accumulator (ROPS version)

The accumulator is equipped for Rops model.



## Adjustable blade width

Changing the blade width is as easy as removing one pin by hand.



## Boom cylinder



Located above the boom, the boom cylinder remains safe from damage during breaker or dumping operations.

## Protected front hoses



By running front hoses and service port hoses inside boom and arm, the hoses are well protected from damage. Service port hoses are hidden inside the boom.

## 2 pattern selection system

The two pattern selection system is standard equipment, allowing the operator to select familiar operating control pattern.





## Fast and easy maintenance



A full-open bonnet and new engine layout makes daily inspection and maintenance of essential components a snap.

## Service indicator



Individual indicator provide you of diagnostic information.

## Specifications

Model		U10-3
Bucket capacity	m <sup>3</sup>	0.022
Std.bucket width: (with/without cutting edge)	mm	368/350
Operating weight	kg	980
Dimensions (intransport condition)	Overall length	mm 2,985
	Overall height	mm 1,380(2,230(with fold 1,655))
	Overall width	mm 750/990
	Min.ground clearance	mm 140
Engine	Model	Kubota D722-E3-BH6
	Total displacement	L(mL) 0.719(719)
	Output	kW(HP)/rpm 7.4(10.2)/2,050
Working range	Max.digging height	mm 3,055
	Max.dumping height	mm 2,215
	Max.digging depth	mm 1,800
	Max.vertical digging depth	mm 1,550
	Max.digging radius	mm 3,380
	Boom swing angle (Left/Right)	degree 55/55
	Min.turning radius (W/o swing/With swing)	mm 1,250/1,075
	Min. tail turning radius	mm 500
Hydraulic system	Pump capacity	L/min 10.5×2/3.1×1
	Auxiliary hydraulic flow	L/min 21
	Max. bucket breakout force	kN(kgf) 10.4(1,060)
Track type		Rubber
Shoe width	mm	180
Travel section	Crawler length	mm 1,340
	Tumbler distance	mm 1,010
	Truck gauge	mm 570/810
	Travel speed (Low/High)	km/h 2.0/4.0
	Gradeability	degree 30°
Swing speed	rpm	8.3
Blade	Width	mm 750/990
	Height	mm 200
	Max. lift above ground/drop below ground	mm 215/190
Hydraulic pump type		2+1 Gear
Swivel motor type		Orbit motor
Travel motor type		Orbit motor
Fuel tank capacity	L	12
Hydraulic oil (reservoir/system)	L	12.5

\* < > with Rops

\*The company reserve the right to change specifications without notice.

## Anti-collision structure hood



The hood is located inside the rotating part to prevent damage by accidental collision.

## Two-piece dozer hose



Two-piece hose connections for the dozer simplify hose replacement, reduce downtime.


## Handy toolbox



The U10 comes complete with a toolbox located under the operator's seat.

## Working Range

Unit : mm



陸機械私人有限公司  
**LAND EQUIPMENT PTE LTD**  
 23 JOO KOON ROAD SINGAPORE 628980  
 TEL: (65) 6862-5223 FAX: (65) 6861-5223  
 E-mail: sales@land-equipment.com.sg  
 Website: http://www.land-equipment.com.sg